




SUOCC

Multimaterial vertical cutter

Sword is an entry-level vertical cutting system designed and based on the real needs of the little-medium sign makers, stand organizers and shops, industrial and crafts companies with high cutting volumes. Very light and user friendly together with an exceptional power of cutting and many other innovative functionalities to work any kind of panels and media aluminium included. A dream that comes true!



Fixed blade "1"
Thickness from 1 to 30mm.



Fixed blade "2" Thickness from 1 to 10mm.

With foot adjustment and blade guide.

You carry out the cut in two steps
1) from up to down 2) Down to up

Millimetric scales for a perfect material alignment.



Blade "3" Optional.





Is the only 100% Italian and Italy-based manufacturer of UV inkjet printing technologies with the capacity and potential to design and build totally machines that produce.



THE FACTORY

R&D + Prototyping

•

Manufacturing

Assembly & Logistics



HOW WORK

- Design & prototyping
- Cutting of raw plate
- Folding
- Welding
- Varnishing
- Quality control of semiprocessed materials
- Pre-assemblage of subgroups
- Final assemblage
- Testing
- Final quality control
- Delivery



ff The max versatility for a world of graphic applications on both rigid and flexible.



Foam





Forex



Dibond




Film



Foam Kmount



Reboard



Glass



Plexiglass



Leather



Plastic expanded

COME, SEE AND DISCOVER our production processes.

TEST WHAT YOU WANT Is that suitable for you?

CHOOSE THE DETAILS And the finishes you like the most.

BRING IT AT HOME o we deliver it to you!!

TRAVEL, BOARD and lodging are included.*



Live the experience !!!



*You can ask for info and existing conditions when you fix an appointment for your visit. Subject to availability.



Fixed blade "1" Thickness from 1 to 30 mm.

Materials:

- Cardboard
- Foam Kmount
- ✓ Gato foam
- Spongy media
- ✓ Plastic expanded

polhvurethane

- ✓ Film
- Plastic alveolar
- Reboaed



Fixed blade "2" thickness from 1 to 10 mm.

Materials:

- ✓ Leather
- ✓ Forex
- ✓ Plastic from 0,5mm.

You carry out the cut in two steps:

- 1) from up to down.
- 2) Down to up



"3" Optional.

Blade for Dibond thickness from 1 to 4 mm. Vcut blade thickness from 5 mm to 30 mm.

Materials:

- ✓ Reboard
- ✓ Spongy media
- ✓ Plastic expanded

Blade Glasscut: glass from 1 to 2 mm Blade PlexCut: plexiglas from 1 to 3 mm

Main features:

- Millimetric base for tool positioning.
- + Light body frame but strong and reliable.
- + Quick tools change: with two units always installed and a third optional
- + Two rotary blades: one moving and one fixed for forex e foam.
- + Tool for dibond and aluminium cut.
- ◆ V-cut tool for cardboard angular cut at 60° and 90°
- + Diamond wheel for glass engraving.
- + Oversize and strong support base to feed big dimensions panels
- + Available in two heights: 165 or 210 cm.



NEOLT FACTORY

Via G. Galilei, 8 24036 Ponte S. Pietro (BG) ITALY

Tel: 035468811

Fax: 035468886

E-mail: info@neolt.it

www.neoltfactory.com



